

State of Utah
Utah Department of Transportation
Motor Carrier Division
4501 South 2700 West, Box 141210
Salt Lake City, Utah 84114-1210

## **For Additional Information Contact:** Adam Anderson, HQ Supervisor

Phone: (801) 964-4508 or Adamanderson@utah.gov



## **Pilot / Escort Vehicle Inspection & Checklist**

Company Name Page 1 / 2											
	Drivers Name	Drive	er's License	Number	State		Expiration Date				
Vehicl	e License Plate Number		Expirat								
	Company Add		City					Zip			
Phone Nu	ımber	Email Address		Dat Ins							
Pilot / Escort Inspection Instructions											
<ol> <li>Items listed in Section One are mandatory for pilot/escort vehicle to operate in Utah. Pilot/escort vehicles and/or operators missing any of these items will be ineligible to operate in Utah until item(s) are corrected.</li> <li>Items listed in Section Two are required however, if not present at the time of inspection pilot / escort vehicles may be passed with conditions and may be approved for a single trip only.</li> <li>Driver must carry driver certification cards and a copy of the most current inspection with them at all times</li> </ol>											
	Action T	aken		Date							
	Passed inspe	1	Agent Signature								
		ction with conditions. Authorized to ent trip only.	ns.	. Badge No.							
		tion. Ineligible to escort vehicle in Ut e corrected.	tah	Port of Entry							
Driver	s Signature		Date								
Comments: (include permit #, route, load description, and all violations.)											

Copy 1: Motor Carrier Division

Copy 2: Port of Entry File

Copy 3: Driver (Must be kept in vehicle and available for inspection)

Company Name:										D	Date			Page 2/2		
Section One  Mandatory equipment and credentials necessary to operate Pilot/Escort											Regulatory					
		Υ	N	vehicles in Utah. Company ineligible to operate pilot / escort until items are corrected.										İ	Guidance	
				Standard 18" or 24" red/white "STOP" and black/orange "SLOW" paddle signs											Construction zone flagging requires a 24" sign	
				n/a UDOT approved Flashlight with red or orange cone										Ti	Mandatory for night time moves	
Equipm	nent			n/a  Height pole made of a non-conductive, non-destructive, flexible or frangible material									j	Required only when escorting a load exceeding 16' in height		
				Class two orange safety vest		N	Tire ja				]	N□ Spare tire		)	N/A	
				Spare "oversize load" sign, 7' x 18" Y□ N□							Orange Hard Hat					
					)		Y□ N□			ı	Fire extinguisher			(1) Must be clearly labeled		
Driver				18 years of age or older		Υ□	N□	,	Valid dri licens			Υ□	N□	Verifie	d	N/A
				Proof	of P / E Cer Card	Expira Dat					Certif	Certification State			N/A	
Vehicle	•			95" minimum wheelbase				12,000 GVW maximum Y				N	Is vehicle towing a load? (2)			(2) Not Allowable
Signing					ayed "ove n roof mou		" Y_					sst be 5' x 10 ", yellow w/ ck lettering 8" x 1"			(3) Bumper mounted signs will receive a failed inspection.	
					ole by oncor		Y	1	N□ Two way				ay radio capabilities			N/A
Lightin	g			Two 6" flashing AAMVA lights one mounted on each side, or one rotating AAMVA approved flashing beacon/light bar											N/A	
Insurance				Proof of valid Insurance (\$750,000 minimum liability) (4)											(4) This is not a cumulative amount	
Comm.	m. Handheld radio, two way radio or (5) other form of communication								(5) For outside vehicle use							
Vollido dos																
Section Two  Pilot /Escort Vehicles missing 25% or less of any items in Section Two will be passed with conditions and will be authorized for a single trip only.  If driver receives two or more No's driver will fail inspection.										Regulatory Guidance						
Υ	N		Nine reflective triangles									N	Must have minimum of			
				Nine reflective triangles										7 for conditional inspection.		
		Eight red burning flares, glow sticks or equivalent illumination device approved by the Motor Carrier Division, UDOT. A combination of burning flares, glow sticks or equivalent illumination device equaling eight will meet minimum requirements.									N	Must have minimum of 6 for conditional inspection				
		Three 18" high orange cones									N	Must have a minimum of 2 for conditional				